ThinkPad T440 Platform Specifications

Positioning	Mainstream Ultrabook™ or Thinbook; one spindle						Keyboard	6-row, spill-resistant, multimedia Fn keys,	optional LED backlight	
Processor	4th Generation In						UltraNav™	TrackPoint® pointing device and Mylar surface touchpad,		
	Danasan Hafi Hafi Basa May Tuba Managan Busasan						ThinkLight™	integrated five buttons, multi-touch None		
		Threads	Frequency		Speed	Graphics	WLAN ⁴	One of the following, configurable by model:		
	i3-4010U		1.7 GHz	- 3MB				 ThinkPad 11b/g/n, 2x2, Wi-Fi + Bluetooth combo adapter, M.2 card Intel Wireless-N 7260, 2x2, Wi-Fi + BT combo adapter, M.2 card 		
	i3-4030U		1.9 GHz	- 3MB	-					
	i5-4200U i5-4210U 2	4	1.6 GHz 1.7 GHz	2.6 GHz 3MB 2.7 GHz 3MB	DDR3L-1600	Intel HD graphics		 Intel Dual Band Wireless-N 7260, 2x2, V Intel Dual Band Wireless-AC 7260, 2x2, 		
	i5-4300U	4	1.7 GHz	2.9 GHz 3MB	DDR3L-1600	4400	WWAN (ontional)	One of the following, configurable by model (mu		
	i7-4500U		1.8 GHz	3 GHz 4MB	1		WWW. (optional)	Wireless WAN upgradable	adding exclusive with with 2005).	
	i7-4600U		2.1 GHz	3.3 GHz 4MB				Wireless WAN, Sierra Wireless EM7355 HERA / EVDO/CSM/CRRS/EDGE CR8		
Memory	8GB or 12GB* max ⁷ / PC3-12800 1600MHz DDR3L, non-parity, dual-channel capable*, 4GB memory soldered to systemboard on selected models, one 204-pin SO-DIMM socket <i>(*for the models with 4GB on-board memory)</i>							 HSPA+/EVDO/GSM/GPRS/EDGE, GPS, M.2 card (US models) Wireless WAN, Ericsson® N5321, HSPA+ 21Mbps/GSM/GPRS/EDGE, GPS, M.2 card (WE models) Wireless WAN, Sierra Wireless EM7345, Intel 4G LTE/HSPA/GSM/GPRS/EDGE, GPS, M.2 card (WE models) 		
Optical	None						OIM			
Storage	Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high, removable, upgradable Some: HDD / SATA 6.0Gb/s, 2.5" wide, 7mm or 9.5mm high, removable,							One of the following, configurable by model: • AT&T® or Verizon® LTE (4G), contract required with service provider (US models)		
	upgradable, Shock Mounted Hard Drive, Active Protection System™						(optional)	 Lenovo SIM, out-of-box service, pay-as-you-go via credit card, no contract required (WE models) 		
	Some: SSHD with 8GB NAND flash memory					art card reader				
M.2 SSD	Some: Single-sided M.2 SSD, via M.2 card slot, exclusive with Smart card reader Some: Double-sided M.2 SSD, via M.2 card slot, exclusive with WWAN card						D1 1 11 711	User selectable, contract required with service provider		
Widescreen	Some: 14.0" (355mm) HD (1366x768), anti-glare, LED backlight,						Bluetooth™ Ethernet	Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter Non-vPro model: Intel Ethernet Connection I218-V (Clarkville)		
display	200 nits, 16:9 aspect ratio, 350:1 contrast ratio							vPro model: Intel Ethernet Connection I218-LM (Clarkville) Optional: Near Field Communication		
	Some: 14.0" (355mm) HD+ (1600x900), anti-glare, LED backlight,					,	NFC			
Multi-touch	250 nits, 16:9 aspect ratio, 400:1 contrast ratio Some: Capacitive-type multi-touch, supports 10-finger gesture							Power-on password, hard disk password, supervisor password, security keyhole		
Camera	HD720p resolution	720p resolution, wide view angle, low light sensitive, face tracking, fixed focus					Security chip vPro (optional)	Trusted Platform Module, TCG 1.2-compliant Intel vPro Technology		
Graphics	Intel HD Graphics 4400 in processor only, or							r Optional: Fingerprint reader on the keyboard bezel, swipe sensor		
	Intel HD Graphics 4400 in processor and NVIDIA GeForce® GT 720M, PCI Express® x8, 1GB memory, NVIDIA® Optimus™ technology; supports external analog monitor via VGA and digital monitor via Mini DisplayPort;					20M,	Limited warranty ¹	d warranty ¹² One of the following, configurable by model:		
						lini DisplayPort;		 1-year depot repair service 3-year/1-yr battery depot repair service 3-year/1-yr battery limited onsite service²⁴ 		
	supports three independent displays;									
	Max external resolution: 1920x1200@60Hz (VGA); 3840x2160@30Hz (DisplayPort via Mini DisplayPort cable on integrated models);					rated models).		3-year/1-yr battery limited onsite service, OID (Onsite International Delivery)		
	2560x1600@60Hz (DisplayPort via Mini DisplayPort cable on optimus models)							Windows® 7 Professional 64 Some: Windows 8 / 8.1 64-bit		
Dimensions ³	14.0W" (WxDxH): 13.35" x 9.15" x 0.83"; 339mm x 232.5mm x 21mm 14.0W" MultiTouch (WxDxH): 13.35" x 9.15" x 0.91"; 339mm x 232.5mm x 23mm							preinstalled through downgrade some: Windows 8 / 8.1 Pro 64-bit Lenovo Solution Center		
Weight ²	Models	II (VVXD)	3-cell + 3-cell			3-cell + 6-cell		Lenovo Solution Center Lenovo Support Think/entage Breduct Because Lenovo Companion		
	Integrated Non-Mui	ltiTouch		9 lb / 1.72kg	4.10 lb /			 ThinkVantage Product Recovery Rescue and Recovery™ Lenovo Companion ThinkVantage System Update 		
	Integrated MultiTou	d MultiTouch		4.03 lb / 1.83kg	4.33 lb / 1.97	1.97kg	-	 ThinkVantage System Update Lenovo Reach (Windows 8.1) 	 Lenovo Reach (Windows 8.1 model) 	
	Optimus Non-Multi			3.73 lb / 1.69kg	4.04 lb /	-			 Hightail - Metro (Windows 8.1 model) Lenovo Cloud Storage by SugarSync 	
	Optimus MultiTouch 3.97 lb / 1.80kg 4.33 lb / 1.97kg						1	Adobe® Reader® - Metro (Windows 8 model)		
Case material	Glass-Fiber Reinforced Plastic • Nitro Pro • Lenovo Cloud Storage by Sugar									
Internal battery External battery	Optional: Integrated Li-Ion or Li-Polymer 3-cell (23.5Wh), HW Authentication Li-Ion 3-cell (23.5Wh) or 6-cell (47.5Wh or 72Wh), HW Authentication							 Evernote® (Windows 8 model) Skype™ PC Device Stage 		
Max battery life ¹⁰	Models 3-cell + 3-cell 3-cell + 6-cell 47.5Wh 3-cell + 6-cell 72Wh							 Microsoft® Office preloaded; AccuWeather 		
,	Integrated		6 hr	12.9 hr		7.2 hr			Amazon Kindle	
	Optimus	7.	7 hr	11.6 hr		i.4 hr			Nitro Pro Evernote	
AC adapter	Integrated model	s: 45-wat	t AC adapte	er; <i>Optimus mo</i>	odels: 65-wat	t AC adapter		,	 Skype 	
Chipset Intel SoC (System on Chip) platform]		 Rara Streaming Norton Studio 		
Smart card reade Media reader	reader <i>Optional:</i> Smart card reader, exclusive with M.2 SSD er 4-in-1 reader (MMC, SD, SDHC, SDXC)							 Microsoft Office preloaded; 		
Ports Two USB 3.0 (one Always On), VGA, Mini DisplayPort, Ethernet (RJ-45),								purchase a product key to activate		
	Dock connector (integrated models only)								 Norton Internet Security (30 days of virus definitions) 	
Audio support	stereo speakers, 1W x 2 / dual array microphone, combo audio/microphone jack						Mil-Spec test	MIL-STD-810G military certification	(00 days of virus delititions)	
							Environment	EPEAT™ Gold (US) or EPEAT Silver (WE);		
								ENERGY STAR® 6.0; GREENGUARD®; RoHS-compliant		